



100% MADE IN THE USA BY PEOPLE WHO CARE!



U.S. DEPARTMENT OF DEFENSE  
PROCUREMENT INSTRUMENT ID No. W58PO5-04-D-0013  
16 PELHAM DAVIS CIRCLE  
GREENVILLE, SC 29615  
① 1 (864) 281.0702  
FAX 1 (864) 297.4132

## G4-B 1 1/2' MESH PRODUCT SPECIFICATIONS

COLOR: BLACK

UV INHIBITOR: 2% ULTRA FINE GRADE CARBON BLACK, FIBERLOKS COATED

HIGH TENACITY POLYESTER MULTIFILAMENT

LENGTH STRETCHED: 3.170" / 80.5MM

DIAMETER: 2.096" / 53.27MM ROUND AT AVERAGE

ELONGATION AT BREAK: 14.0+ / -3.0%

SHRINKAGE IN HOT AIR: 8.0+ / -1.5%

MELTING POINT: 472 DEGREES F

HEAT DISTORTION TEMP: 360 DEGREES F

WIND LOAD: 4.0%

TENACITY: 7.5 GRAMS PER DENIER MINIMUM

8.5 GRAMS PER DENIER MINIMUM

BREAKING STRENGTH: 110 LBS PER MESH ON AVERAGE, WEFT DIRECTION

121 LBS PER MESH ON AVERAGE, WARP DIRECTION